






AUTOMATES DE MESURE

HIMOS

Modèle		Display/ Format	Touches/ LED's	Entrées Numériques	Sorties Numériques	Entrées Analogiques	Sorties Analogiques	Ports Série	Ethernet	USB + Compact Flash
HI 125P		128 * 64(1.25") LCD-Monochrome 48x48x76mm	8/0	8	8	--	--	2	--	--
HI 126P		128 * 64(1.25") LCD-Monochrome 48x48x76mm	8/0	6	6	1 (Univ.) 12bit	1 (4-20mA) 12bit	2	--	--
HI 300P		128 * 64 (3") LCD-Monochrome 183x101x37mm	18/4	16	12	--	--	2	--	--
HI 301P		128 * 64 (3") LCD-Monochrome 183x101x37mm	18/4	16	2 PWM 10 relais 2A@230V	--	--	2	--	--
HI 302P		128 * 64 (3") LCD-Monochrome 183x101x37mm	18/4	16	12	4 (Univ.) 12bit	2 (4-20mA) 12bit	2	--	--
HI 303P		128 * 64 (3") LCD-Monochrome 183x101x37mm	18/4	16	2 PWM 10 relais 2A@230V	4 (Univ.) 12bit	2 (4-20mA) 12bit	2	--	--
HI 410P		192 * 64 (4") LCD-Monochrome 140x77x35mm	Écran tactile	16	12	--	--	2	--	--
HI 411P		192 * 64 (4") LCD-Monochrome 140x77x35mm	Écran tactile	12	8	4 (mA)10bit 2 (Univ.)12bit	1 (4-20mA) (0-10V)	2	--	--
HI 412P		192 * 64 (4") LCD-Monochrome 140x77x35mm	Écran tactile	16	12	2 (Univ.) 12bit	--	2	--	--
HI 570		320 *240(5.7") STN-16 tons de gris 197x139x52mm	Écran tactile	--	--	--	--	2	--	--
HI 572RP		320 *240(5.7") STN-16 tons de gris 197x139x52mm	Écran tactile	28	2 PWM 14 relais 2A@230V	--	--	2	--	--
HI 573RP		320 *240(5.7") STN-16 tons de gris 197x139x52mm	Écran tactile	28	2 PWM 14 relais 2A@230V	4 (Univ.) 12bit	2 (4-20mA) (0-10V)	2	--	--
HI 575		320 *240 (5.7") STN couleur 197x139x52mm	Écran tactile	--	--	--	--	2	--	--
HI 576		320 *240 (5.7") STN couleur 197x139x52mm	Écran tactile	--	--	--	--	2	1	--
HI 577P		320 *240 (5.7") STN couleur 197x139x52mm	Écran tactile	28	16	4 (Univ.) 12bit	2 (4-20mA) (0-10V)	2	--	--
HI 577RP		320 *240 (5.7") STN couleur 197x139x52mm	Écran tactile	28	2 PWM 14 relais 2A@230V	4 (Univ.) 12bit	2 (4-20mA) (0-10V)	2	--	--
HI 578RP		320 *240 (5.7") STN couleur 197x139x52mm	Écran tactile	28	2 PWM 14 relais 2A@230V	--	--	2	--	--
HI 1200		800 *600(12.1") TFT-Couleur 312x246x44mm	Écran tactile	--	--	--	--	2	--	--
HI 1202		800 *600(12.1") TFT-Couleur 312x246x44mm	Écran tactile	--	--	--	--	2	1	1




Legros sas

ZI Portuaire - BP 93 - bld de Chatillon
62202 BOULOGNE SUR MER CEDEX
Tél : 03.21.83.36.81 - Fax : 03.21.83.21.29

Site : www.legros.fr

Email : legros@legros.fr - commercial@legros.fr

MODULES ENTRÉES/SORTIES (Rail DIN)

Modèle	Dimensions 70x100x35mm	Entrées Numériques	Sorties Numériques	Entrées Analogiques	Sorties Analogiques	Ports Serie
HI 42A		--	--	4 (Univ.) 12bit Pt-100, TC 0/4-20mA 0-10V 0-50/100mV	2 (V, mA) 12bit 0-10V 4-20mA	1
HI 80AL		--	--	8 (V, mA) 12bit 0-10V 4-20mA	--	1
HI 0808R		8	8 relais 2A@230VAC	--	--	1

ACCESSOIRES

14000242	Mémoire Compact Flash 256Mb
14000243	Adaptateur USB <-> RS232C (DB9)
19500021	Cable Programmation RS232 de PC (DB9) <-> HIMOS (DB9)
19500022	Cable Programmation RS232 de PC (DB9) <-> HIMOS (RJ45)
19500023	Cable Connection RS2 KOSMOS (RJ11) <-> HIMOS (DB9)
19500024	Cable Connection RS4 KOSMOS (RJ12) <-> HIMOS (DB9)
19500025	Cable Connection RS2 KOSMOS (RJ11) <-> HIMOS (RJ45)
19500026	Cable Connection RS4 KOSMOS (RJ12) <-> HIMOS (RJ45)
19500027	Cable Connection PLC SIEMENS S7-MICRO <-> HIMOS (DB9)
19500028	Cable Connection PLC SIEMENS S7-MICRO <-> HIMOS (RJ45)
19500029	Cable Connection PLC OMRON HOSTLINK <-> HIMOS (DB9)
19500030	Cable Connection PLC OMRON HOSTLINK <-> HIMOS (RJ45)
19500031	Cable Connection TELEMECANIQUE (TSX07/37)/HIMOS(DB9)
19500032	Cable Connection TELEMECANIQUE (TSX07/37)/HIMOS(RJ45)

LOGICIEL

HIMOSOFT	Logiciel de programmation gratuit disponible sur http://www.ditel.es
-----------------	--

Legros sas

ZI Portuaire - BP 93 - bld de Chatillon
 62202 BOULOGNE SUR MER CEDEX
 Tél : 03.21.83.36.81 - Fax : 03.21.83.21.29
 Site : www.legros.fr
 Email : legros@legros.fr - commercial@legros.fr